



Hygienic Wash Stations & Doorsets
Doorsets built for demanding environments

Hygidoor Tuff

- 68 **Introduction to Hygidoor Tuff**
- 70 **Hygidoor Tuff colours & finishes**
- 71 **Hygidoor Tuff specification**

Introduction to Hygidoor Tuff

Demanding environments such as schools, restaurants and hospitals benefit from Hygidoor Tuff, which is built to withstand heavy use and vandalism.

With a high density particleboard core and flush glazing as standard, Hygidoor Tuff has a unique feature, it is clad in Trovex Resilience, a textured hygienic wall cladding that minimises the impact of knocks and scrapes. This is critical in high-traffic areas, to preserve the aesthetic appearance of the Hygidoor Tuff, extend its lifespan and reduce maintenance costs.

Call **01707 254 170** and speak to a member of the team.



Trovex Resilience in use on Hygidoor Tuff

Applications

Built to last, Hygidoor Tuff minimises the impact of knocks and scrapes. It's ideal for use in leisure facilities, gymnasiums, school, healthcare environments and many other situations.



Leisure centres and gymnasium



Schools



Healthcare

Hygidoor Tuff colours & finishes



Material samples of any colour are available for rapid despatch to a specified address, making it easy to check and confirm your choices. **Call 01707 254 170**

Available colours and finishes, see pages 84 - 89 for details:

Resilience Textured

Hygidoor Tuff specification

L20	Doors / Shutters / Hatches
480	PROPRIETARY HYGIENIC PVC HYGIENIC DOORSETS
Manufacturer	Trovex, Axiom House, Travellers Close, Welham Green, AL9 7JL Tel: 01707 254 170, Email: sales@trovex.com
Product ref	Trovex Hygidoor Tuff encapsulated with Trovex hygienic PVC.
Substrate	Frame to be set into correct aperture in suitable solid structural wall or partition.
Preparation	Wall substrates must be structurally sound and capable of supporting the frame and door assembly.
Fixing method	Frame to be fixed to structural wall using proprietary fixings (not supplied). Door leaf prehung on frame.
Size	Height - Standard 2044mm Width - Standard 906mm Thickness - Standard 48mm
Colour	Standard Diamond White or selected from Trovex colour collections.
Frame & architrave	Architrave detail integral to frame (preformed or flush).
Glazing/Infill	Standard square, Hygiglaze™ flush glazed / fire-rated / vision panel. Hygivision™ control panels to consulting / clinic rooms, with thumbturn to inside, key control to outside.
Joint treatment	Seal frame to wall with approved sealant. For flush frames: use supplied joint profile or welded joint system.
Ironmongery	Refer to Ironmongery Schedule.
Components/ Accessories	Standard stainless steel hinges. Options of flush hygienic vision panels, self-closing mechanism and fire rated core FD30 and FD60.
Included features	Fully encapsulated with thermoformed external corners, intumescent / smoke seals.

The above specifications represent typical installations. For any other details or specifications, call our technical team on 01707 254 170

riba
product
selector

